



INDUSTRIAL SCALES

U TYPE PORTABLE PALLET SCALES



- EC Type approval
- Various Capacity options from 300 kg up to 3000 kg
- Practical pallet weighing with U type design
- Easily Portable Light Platform Scale with wheels and carry handle
- Opportunity to communicate with computer
- Printing Ticket and – Label through printer connection
- Reporting and recording possibilities








U type portable scales especially designed for the materials which are carried, loaded and stocked with forklift and transpallet in mainly food sector companies, transport companies, cold storage areas, international transport warehouses, shopping malls and chemical industry. Owing to light design, wheels and carry handle, it can be carried easily and quickly in the plant. Pallets which carried by transpallet can be easily loaded to platform to weigh.

Beside to their basic features like tare, automatic, semi-atomic zero, easily readable VFD display and RS 232 serial communication output, they also have many additional weighing functions which enable ticket and label print outs through thermal, ribbon, dot matrix and barcode type printer connections. For filling, dosing and automation applications, U type portable pallet scales have various interfaces and control outputs. For explosive and flammable environments ex-proof models are also available. By connection with Computer or Industrial PC based terminal, U type portable pallet scales allow flexible applications with special software options.



U TYPE PORTABLE PALLET SCALES



TECHNICAL SPECIFICATIONS

PLATFORM

Model	WP-U
Material	Steel
Environmental Protection	IP 65 (Standard)-IP 67 / IP 68 (Option)
Load cell	4 pcs, OIML R60 C3 Class
Load cell Protection Class	Steel IP 67 (Standard) / Stainless Steel IP 68 (Option)
Platform Material Options:	CSS: Complete Stainless Steel

WEIGHT INDICATOR

Model	LL3
Class	III / IIII
Caseing	Aluminium Cast (Standard) Stainless Steel (Option)
Protection Class	IP 54 / IP 65
Display	7 Dijit, 14 mm. VFD Display Zero, Net, Kg, Weight Range, Stand Still Load Symbols
Keypad	Membran type, 20 functional alphanumeric keys (Programming, Calibration, Zero, Tare, Printing, Reporting)
Operation Voltage	220 VAC / 12 VDC
Operation Temp. Range	- 10°C ... + 40°C
Serial Communication	RS232
Options	<ul style="list-style-type: none"> • 1 x RS232, 1 x RS 422/485 • RF Communication • 2MB. (105.000 Record) Alibi Memory • Operating with Battery

CAPACITIES AND DIMENSIONS

MODEL CODE	CAPACITY X DIVISON	DIMENSION
WP-U- 300K.4L	300 kg X 100 g	97 X 125 X 9 cm
WP-U- 600K.4L	600 kg X 200 g	97 X 125 X 9 cm
WP-U-1500K.4L	1500 kg X 500 g	97 X 125 X 9 cm
WP-U-3000K.4L	3000 kg X 1 kg	97 X 125 X 9 cm

OPTIONS



LL2-WT-L Weighing Terminal



Touch-Operated Weighing Terminal



Printer



Indicator Connector Column



Remote Display



RF Communication Kit